

Specifications		SRP-770II
Printing Method	Direct Thermal line Printing	
Print Speed	Max. 127 mm/sec (5.1 Inches/sec)	
Resolution	203 dpi (8 dot/mm)	
Character Set	7 Resident bitmap fonts	
	7 Code Page, expandable up to 4X	
	Soft font storage	
	BMP & PCX Graphic Support	
Bar-code type	UPC-A/E, JAN-13/8, ITF, Code 39, Code 128, CODABAR, Code 93, Interleave 2 of 5, UCC-EAN128. 2D Codes: QR Code, Maxicode & PDF417	
Emulation	ESC/POS, EPLII & ZPLII	
Paper Type	Labels, Tag, Continuous & Fan fold	
Paper Width	25.4 ~ 101.6 mm	
Roll Diameter	Core: 25.4 ~ 38.1 mm	
	Roll outer ? Max. 130 mm	
CPU	32 Bit	
Receive Buffer Size	32 Kbyte	
Flash Memory	2 Mb	
Interface	Serial	RS-232C
	Unidirectional Parallel	IEEE 1284
	USB	
	Ethernet	
Power	24 DCV, 2.3A, External power supply	
External Dimensions (WxDxH)	184 x 221 x 171 mm	
Reliability	Head	50,000,000 Pulse (Approx. 50Km)
	Mechanism MCBF	20,000,000 Lines
Safety Standards	UL, C-UL, FCC Class A, TUV-GS, CE Marking	