

Specifications		SLP-D420 Series	
Printing Method	Direct Thermal Printing		
Print Speed	Max. 152 mm/sec (6 Inches/sec)		
Resolution	203 dpi (8 dot/mm) (300Dpi optional)		
Paper	Types: Gap, Notch, Black Mark, Continuous, Fan-Fold		
	Width: 25~116 mm		
	Core: 25.4~38.1 mm		
	OD: Internal ? 130 mm, Core ?25.4~38.1mm		
Character Set	Alpha Numeric Character: 95		
	Extended Character: 128 x 23 Pages		
	International Character: 32		
	Resident Bitmap Fonts:10 True Type Fonts: 0		
Bar-code type	1D Codes:EAN-8, EAN-13, UPC-A/E, ITF, Code 39, Code 128, Code 93, Interleave 2 of 5, Coda Bar 2D Codes: QR Code, Maxicode, Datamatrix & PDF417		
Emulation	SLCS, EPLII & ZPLII		
Sensor	Transmissive Sensor, Reflective Sensor		
Interface	Serial		RS-232C
	Unidirectional Parallel		IEEE 1284
	USB		USB 2.0
	Ethernet		Optional
Power	24 DCV, 3.75A, External power supply 100~240V		
External Dimensions (WxDxH)	194 x 243 x 171 mm		
Weight	Approx. 5.7 Kg		
Reliability	MCBF		10 million lines
	Head		25 Km
	Auto Cutter Option		300,000 cuts
Safety Standards	UL, C-UL, FCC Class A, TUV-GS, CE Marking		