

## Specifications- DLPBT7100PKIT

<b>Bluetooth Technology</b>	Bluetooth 2.0 Certified Class 1 Radio Frequency 2.40 to 2.48 GHz Radio Range (Open Air) 100.0 m
<b>Sensor</b>	Linear Imager Aiming: 630-680 nm VLD
<b>Light source</b>	Illumination: LED Array 630-670 nm
<b>Scan rate</b>	390 Reads/sec
<b>Resolution</b>	Max. 0.076mm/3 mils
<b>Ambient Light</b>	100,000 Lux
<b>Print Contrast</b>	15% or higher
<b>Reading Indicators</b>	Datalogic 'Green spot' good read, adjustable tone beeper, Good read LED
<b>IP Rating</b>	IP65 Lithium-ion 2400 mAh
<b>Battery</b>	Charge time: 4 hours with external power  Reads per Charge: 22,000 in 16 Hours DLBC7030 - USB, RS232, Wedge & Wand Multi Interface
<b>Interface (base)</b>	DLBC7010 - RS232, IBM 46XX, USB Multi Interface
<b>Input voltage (Base)</b>	4.0-14.0 VDC Operating typical 280mA @ 5V
<b>Input Current (Base)</b>	Standby/Idle Typical 210 mA @ 5V
<b>Operating Temperature</b>	-20 to 50 °C
<b>Dimensions (H x W x L)</b>	Scanner 203 x 76 x 114 mm Base 239 x 117 x 48 mm Scanner 354.4g
<b>Weight</b>	Cradle 326.2g