

PRINT METHOD	9-pin, Serial Impact Dot Matrix
PRINT FONT	
FONT	7 x 9 / 9 x 9
COLUMN CAPACITY (COLUMNS)	40 / 42 or 33 / 35
CHARACTER SIZE (MM)	1.2 (W) x 3.1 (H) / 1.6 (W) x 3.1 (H)
CHARACTER SET	95 Alphanumeric, 37 International, 128 x 12 Graphic, Traditional / Simplified Chinese, Thai, Japanese, Korean
CHARACTERS PER INCH	17.8 / 16 cpi or 14.5 / 13.3 cpi
INTERFACES	RS-232, Bi-directional parallel, Dealer Option: USB, 10 Base-T I/F
DATA BUFFER	4 KB or 40 bytes
PRINT SPEED	
	4.7 lps (at 40 columns, 16 cpi), 6.0 lps (at 30 columns, 16cpi)
PAPER	
DIMENSIONS (mm)	57.5 ± 0.5, 69.5 ± 0.5, 76.0 ± 0.5 (W) x dia. 83.0
THICKNESS (mm)	0.06 to 0.085
COPY CAPABILITY	One original and one copy
INKED RIBBON	ERC-38 (Purple, Black, Black / Red)
RIBBON LIFE	
	Purple : 4 x 10 ⁶ characters, Black : 3 x 10 ⁶ characters, B / R : 15 x 10 ⁵ characters (Black), 75 x 10 ⁴ characters (Red)
POWER	AC adaptor (included)
POWER CONSUMPTION	Approx. 31 W
D.K.D. FUNCTION	2 drivers
RELIABILITY	
MTBF	18 x 10 ⁴ hours
MCBF	18 x 10 ⁶ lines
OVERALL DIMENSIONS (mm)	
	Type A : 160 (W) x 286 (D) x 157.5 (H) Type B : 160 (W) x 248 (D) x 138.5 (H) Type D : 160 (W) x 248 (D) x 138.5 (H)
WEIGHT (APPROX.)	
	Type A : 2.7 Kg Type B : 2.5 Kg Type D : 2.3 Kg
EMC STANDARDS	VCCI class A, FCC class A, CE marking, AS / NZS 3548 class B
POWER SUPPLY	Exclusive AC adaptor (included)
FACTORY OPTION	Near-end sensor
OPTION	Wall-hanging bracket WH-10
SAFETY STANDARDS	UL / CSA / TÜV (EN60950)