

Thermal Receipt Printer

SRP-350



Look no further for thermal printing on 80mm wide paper, the SRP-350 is all you need. Not only for the retail environment but also for medical, warehouse, manufacturing, mail order etc..

Benefiting from Windows and OPOS drivers this great printer is easy to integrate to any system. Fast speed and reliability you can expect from a leading manufacturer. Providing simplicity for the operator with "drop in and print" paper loading and ease of connectivity for the technician with interchangeable interfaces and industry standard drivers. The modern design and small footprint enhance any environment.

BIXOLON®

SAMSUNG

Thermal Printer

SRP-350

- High-end thermal print technology : Quiet printing for a convenient atmosphere in the cash zone. Printer can also be used in high-class shops; avoids disturbing the staff and the customers at POS environment
- High printing speed : The SRP-350 prints at speeds of up to 150mm per second
- Easy system integration : Drives are available for Windows 95/98/ME/NT4.0/XP/2003 server and OPOS
- A simple drop-in loading system means that even inexperienced operators can load paper rolls with the minimum of efforts
- Convenient software program : Logo/firmware download program helps you use logo efficiently and easily
- Various interface cards : The SRP-350 features modular interface, RC-232C, RS-485, Parallel, USB, Ethernet(10/100 Base T), Bluetooth interfaces simply by ordering a new module.
- Easy paper jam clearance
- Barcode printing



Easy Paper Loading



Small space for installation



Attractive Features



SRP-770II

SPECIFICATION FOR THE SRP-350 THERMAL PRINTER

PRINT	PRINT METHOD	Direct Thermal	
	PRINT SPEED	150mm / sec (47.2 LPS)	
	PAPER SUPPLY METHOD	Easy Paper Loading	
	RESOLUTION	180 dpi (7dot / mm)	
	CHARACTER SET	Alphanumeric Character : 96	
		Extended Graphic : 128 x 7 page (1space page)	
		International Character : 32	
CHARACTER SIZE	Font A : 12 x 24 Font B : 9 x 17		
CHARACTER PER LINE	Font A : 42 Font B : 56		
PAPER TYPE	Thermal paper		
PAPER ROLL	WIDTH	79.5 mm ± 0.5mm	
	DIAMETER	Max. φ 83.0mm	
RELIABILITY	MCBF	37,000,000 Lines	
	AUTO CUTTER	1.5 million cuts	
	TPH	100Km	
BARCODES	1D : EAN - 13, EAN - 8, Code 39, Code 93, Code 128, ITF, Coda bar, UPC - A, UPC - E		
	2D : PDF417, QR Code		
EMULATION	ESC / POS		
FLASH MEMORY	16 Mbit		
DRIVER	Windows 95 / 98 / Me / 2000 / NT / XP / 2003 server, OPOS		
SENSOR	2 OPTIONAL	Paper Near End Sensor, Paper End Sensor	
DRAWER PORT	2 ports		
CONNECTIVITY	INTERFACE		
	RS - 232C, IEEE1284, USB, USB + Serial, RS - 485, Ethernet(10 / 100 Base - T), Bluetooth		
OPTIONS	LANGUAGE	Buyer language support	
	WALL MOUNT	RWM - 350	
	COLOR	Ivory, Dark gray	
POWER	SUPPLY	AC120V ~ 230V ± 10% (Include), DC24V, 2.3A	
DIMENSION	145(W) x 195(L) x 146(H) mm		
AUTO CUTTER	TYPE	Guillotine	

BIXOLON®



BIXOLON Co., LTD.
 Factory World 709, 332-2, Wonchon Dong, Yeongtong Gu, Suwon,
 Kyunggi Do, Korea, 442-822 Tel : 82 31 218 5528 Fax : 82 31 218 5589
 E-mail : sales@samsungminiprinters.com
 www.samsungminiprinters.com

Distributed by :

* Design & Specification are subject to change without notice.
 2006. 5