

RT40

INDUSTRIAL MOBILE COMPUTER




- Industrial grade condensation hardware. Equipped with heater of LCD/scan engine. Your cold chain solution.
- Hot-swap battery design, exchanges exhausted battery without reboot. Increase your efficiency.
- Qualcomm Octa-core 2.2GHz high-efficiency processor and cutting-edge Android Q operating system, gives you unparalleled performance.
- 38 keys island-style keyboard + 4" giant touch screen, intuitive operation reaction, accurate even with glove hands. (29 keys optional)
- Built-in industrial-leading scanner engine, captures 1D/2D barcodes on screen and paper even if they are contaminated, wrinkled or distorted. 15m long-range scanner engine is optional.



IP68 Waterproof
1.8m Drop Resistance



Seamless WiFi Roaming
4G Communication



13M Pixel
AF Camera



4" Touch Screen
Corning Gorilla glass



Working Temperature
-25°C~+50°C



U-HOME
Mobile Device
Management Tool Kit

Specification RT40

Basic parameter

| | |
|---------|--|
| CPU | Qualcomm Octa-core 2.2GHz Qualcomm Octa-core 1.8GHz |
| Storage | 3GB RAM/ 32GB ROM 4GB RAM/ 64GB ROM (optional) |
| OS | Android Q (10) |

Basic specification

| | |
|--------------|--|
| Screen | 4 inch 480*800 pixel |
| Dimension | 199 x 58(handle) x29(thinnest) mm (78.34 x 22.83 x 11.41 in) |
| Weight | 425g |
| Main battery | 3.85V 5,200mAh Support battery swap |
| Extension | microSD card, Max.128GB extension |
| SIM | Nano SIM*1, PSAM/ SIM*1 (self-adaption) |
| Buttons | 38 keys isolation keyboard, support wake up (PWR key, front scan key, side scan key, PTT key) (29 keys optional) |
| Voice | Earpiece, speaker, microphone |
| Sensor | Light sensor, proximity sensor, Accelerometer (optional), e-compress(optional), gyro sensor(optional) |

Environment

| | |
|---------------------|---|
| Working temperature | -20° C ~ +50° C (cold chain version -25° C ~ +50° C (-4° F ~ +122° F (cold chain version -13° F ~ +122° F) |
| Storage temperature | -40° C ~ +70° C (-40° F ~ +158° F) |
| Humidity | 5% ~ 95% RH (non-condensing) |
| Drop test | 1.8M flat concrete |
| Tumble test | 1000 times 1m |
| Sealing | IP68 |
| ESD | ±15kV air, ±8kV direct |

DATA CAPTURE

| | |
|----------|---|
| Scanning | High-performance scanner engine,1D/2D barcode and screen barcode scan supported |
| Camera | Rear-13MP auto-focus camera with flash LED |
| NFC | ISO14443 Type A and B; Mifare/FeliCa and ISO15693 cards; Reader mode, P2P mode and Card Emulation |

WIRELESS WAN DATA AND VOICE COMMUNICATIONS

| | |
|----------------------|---|
| Radio Frequency Band | TDD-LTE(B34/B38/B39/B40/B41) FDD-LTE(B1/B2/B3/B4/B5/B7/B8/B12/B13/B14/B17/ B19/B20/B25/B26/ B28A/B28B/B66) WCDMA(B1/B2/B4/B5/B8) GSM/EDGE/GPRS(850/900/1800/1900) TD-SCDMA(B34/B39) CDMA2000 1x EV-DO Rev.A BC0 (800MHz) CDMA 1x GSM/EDGE/GPRS(850/900/1800/1900) |
| GNSS | GPS(A-GPS), Beidou, Glonass, Galileo |
| VoLTE | Support Vo-LTE HD video & voice call |

WIRELESS LAN

| | |
|-------------------------|---|
| Radio | IEEE 802.11a/b/g/n/ac (2.4G/5G WIFI) |
| Operating Channels | 2.4G: CH1~CH13 5G: CH34-CH140, CH149~CH165 |
| Security and Encryption | WEP, WPA/WPA2-PSK(TKIP and AES), EAP-TLS, EAP-TTLS, PEAP-MSCHAPv2, PEAP-TLS, PEAP- GTC, PWD, SIM, AKA |
| Fast Roaming | PMKID caching, 802.11r, OKC |

WIRELESS PAN

| | |
|-----------|------------------|
| Bluetooth | BT5.0+BR/EDR+BLE |
|-----------|------------------|

Optional Accessories



Pistol grip version



Single Cradle



Hand Strap



Multi-Functional Cradle

Urovo Technology Co., Ltd.

- Tel: 86 755-22673926
- Website: en.urovo.com
- E-mail: urovo@urovo.com
- Address: Room 613,6/F.,Asia Trade Centre,79 Lei Muk Road,Kwai Chung,N.T.,Hong Kong

* This page is subject to change without prior notice