

### PX-610II

Thermal Receipt Printer



Introducing the Nexa PX-610II, the next generation in high-performance thermal receipt printers. This state-of-the-art device is designed to meet the demands of high-volume retail and hospitality environments.

The Nexa PX-610II offers a sleek, compact design without compromising on functionality. With a print speed of up to 250mm per second, it ensures quick, efficient service, even at peak times. Its high-resolution printing capabilities deliver crisp, clear receipts that enhance customer satisfaction.

The Nexa PX-610II is equipped with easy-to-use features such as drop-in paper loading and an auto-cutter, making it a reliable choice for businesses of all sizes. It supports multiple interfaces, including USB, Serial, and Ethernet, for seamless integration into existing systems.

With its robust construction and high reliability, the Nexa PX-610II is built to last, offering an exceptional return on investment. Experience the difference with the Nexa PX-610II – the ultimate solution for your receipt printing needs.



Triple Interface  
Ethernet + USB  
+ Serial



Fast 250mm/sec  
print speed



Optional advance  
replacement warranty  
upgrade available

### Specifications

Printing Speed	250mm/s
Resolution	203dpi
Printing Method	Thermal
Effective Printing Width	72mm (on 80mm paper)
Character Sets	Alphanumeric: 95 Extended Graphics: 128 x 35 page International: 32
Character Size	Font A: 12 x 24 Font B: 9 x 17 KOR, CHN, JPN: 24 x 24 KOR, CHN, JPN: 21
Character per Line	Font A: 42 Font B, C: 56 KOR, CHN, JPN: 21
Paper Type	Thermal paper
Paper Width	79.5±0.5mm
Paper Roll Diameter	Max: 80.0mm
Paper Supply Method	Drop-in paper load
Auto Cutter Life	1.5 million cuts
Print Head Life	150km
Emulation	ESC/POS™
O/S and Development Tool Support	WIN XP/WIN 7/WIN 8/WIN10/WIN 11/LINUX/Mac
Sensor	Paper End Sensor Optional
Drawer Port	RJ11/RJ12 24V
Interface	USB+Serial+Ethernet
Dimensions	191×140×143mm
Colour	Black
Operating Temperature	0°C—45°C
Operating Humidity	10%—80%
Storage Temperature	-10°C—60°C
Storage Humidity	20%—90% (Paper excluded)
Power Supply (Adapter)	DC 24V, 2.5A

Nexa PX-610II Data Sheet | Rev A | Jan-24. © 2024. Features and specifications subject to change without notice.